

NAME

mailrm – zmailer mail queue message remover

SYNOPSIS

mailrm [*id* ...]

DESCRIPTION

mailrm attempts to remove the locally queued mail messages named on its command line by submitting mail messages that cancel the queued messages.

The *Obsoletes:* message header is the mechanism used to accomplish this. The *router* turns it into a message control file directive that the *scheduler* implements. The *scheduler* will of course do its best to ensure only the owner of a message can cancel it. Therefore this program is only useful to whomever originally sent the message to be cancelled. The super user is not treated specially.

The *id* is the message file id of a to-be-cancelled message, as it is reported by *mailq*. It is not the message id, although that is the information that is actually sought for the *Obsoletes:* header contents. *mailrm* will rummage through message control files in *POSTOFFICE/transport* to retrieve the message id for a given message file id.

ENVIRONMENT VARIABLES**ZCONFIG**

This environment variable is expected to be inherited from the *scheduler*(8zm), and it tells where scheduler's idea of *ZENV*-variables are located at.

FILES

/opt/mail/zmailer.conf (ZCONFIG)
/var/spool/postoffice/transport (POSTOFFICE/transport)

SEE ALSO

router(8zm), *scheduler*(8zm), *mailq*(1zm), *zmailer.conf* (5zm).
RFC987, RFC1138

AUTHOR

This program authored and copyright by:
Rayan Zachariassen <no address>