

**NAME**

`newaliases` – zmailer aliases database rebuilder

**SYNOPSIS**

`newaliases` [ `-s` ] [ `/file/path` ]

**DESCRIPTION**

**This utility has been superseded by `zmailer newdb` mechanism, but can be used in few places, provided that `aliases` type database is being produced with default settings!**

Running the `newaliases(1zm)` without parameters rebuilds the `aliases(5zm)` database used by the `router(8zm)` configuration at most sites.

This script wrapper constructs argument list for underlying `newdb(8zm)` program (and `makedb(8zm)` under it,) which does actual `aliases(5zm)` format database compilation work.

**OPTIONS**

`-s`

Optionally silence the underlying `makedb(8zm)` program.

`/file/path`

Optionally specify file path (fully qualified, or relative) to the database to be compiled.

With this option one can specify which database is to be compiled.

**ENVIRONMENT VARIABLES**

`ZCONFIG`

This environment variable is expected to be inherited from the user's environment for cases where default location isn't correct.

**Z-ENVIRONMENT VARIABLES**

Following *ZENV-variables* are used by the `newaliases(1zm)` program:

`MAILVAR`

Tells where the ZMailer's runtime databases, etc. are by default.

**FILES**

`/opt/mail/zmailer.conf` (`ZCONFIG`)

`/opt/mail/db/aliases` (`MAILVAR/db/aliases`)

**SEE ALSO**

`aliases(5zm)`, `router(8zm)`, `makedb(8zm)`, `newdb(8zm)`, `zbases.conf(5zm)`, `zmailer(1zm)`, `zmailer.conf(5zm)`.

**AUTHOR**

This program authored and copyright by:

Rayan Zachariassen <no address>

Fairly radical rewriting by:

Matti Aarnio <mea@nic.funet.fi>